SKU: GGB-8

UPC: 0783669260205

Features & Benefits:

Description: Permaground Copper Grounding Grid, Conductor Range 500-250, Ground Rod Size 1in, Rebar Size #6, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number Main	998
ILSCOs Die Index Number Tap	998

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	1
Rebar Size(s) Main	#6 (3/4)

Dimensions

Height (IN)	1.697
Height BX (IN)	3.75
Height (mm)	43.1038
Length (IN)	4.597
Length (mm)	116.7638
Weight (LB)	1.3416554048217
Weight BX (LB)	8.3829
Width (IN)	4.525
Width BX (IN)	6.375
Width (mm)	114.935

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366926020

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA

Testing Standards

CSA File Number	LR-5465
CSA Standard	C22.2 No. 41
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating	NA

Color

Color	Copper