



SKU: GGC-2

UPC: 0783669260526

Features & Benefits:

Description:Permaground Copper Grounding Grid, Main Conductor Range 250-1/0, Tap Range 2-4, Ground Rod Sizes up to 5/8in, Rebar Sizes #3-#4, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Catalog Number	ILD-997
ILSCOs Die Index Number	997

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	2 Sol - 4 Sol
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 1/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 4 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	1/2 to 5/8
Rebar Size(s) Main	#3 (3/8)

Dimensions

Height (IN)	2.099
Height BX (IN)	2
Height (mm)	53.3146
Length (IN)	0.937
Length (mm)	23.7998
Weight (LB)	0.312
Width (IN)	0.75
Width BX (IN)	6.1875
Width (mm)	19.05

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper



Additional Technical Specifications

Conductor Type

Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366926052

Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

CSA File Number	LR-5465
CSA Standard	C22.2 No. 41
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating

NA

Color

Color

Copper