




SKU: GMS-4

UPC: 0783669997279

Features & Benefits:

Description:Permaground Copper Ground Clamp to Surface, Conductor Range 500-300, 1 Conductor, 1 Bolt, 1/2in Bolt Size, Single Plate

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	2.614
Height BX (IN)	5
Height (mm)	66.3956
Length (IN)	2.298
Length (mm)	58.3692
Mounting Bolt/Stud Length	2.614
Mounting Bolt/Stud Length (mm)	66.3956
Weight (LB)	0.5
Weight BX (LB)	25.41
Width (IN)	1.4
Width BX (IN)	6.5
Width (mm)	35.56

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Clamping Bolt Size	5/16
Mounting Bolt/Stud Size	5/16



Number of Wire Binding Screws per Port
Wire Binding Screw Size

0
NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366999727

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 300 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA