



SKU: GPL-26

UPC: 0783669262469

Features & Benefits:

Description:Permaground Copper U-Bolt Ground Clamp, Conductor Range 4-8 Sol, Pipe Size 1-1/2in, Ground Rod Sizes 1-5/8 to 1-7/8in, UL, CSA

Specs

Additional Class Attributes

Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	4 Sol - 8 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 8 Str
Ground Rod Size	1-5/8
NPS/IPS Pipe Size	1-1/2

Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	4.165
Height BX (IN)	3.75
Height (mm)	105.791
Length (IN)	3.25
Length (mm)	82.55
Weight (LB)	1.117
Weight BX (LB)	3.546
Width (IN)	1.562
Width BX (IN)	5.25
Width (mm)	39.6748

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Material	Copper
Wire Binding Hardware Material	Silicon bronze

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366926246

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Bolt and Screw Sizes

Clamping Bolt Size	1/4
--------------------	-----