

SKU: GPL-34

UPC: 0783669262629

Features & Benefits:

Description: Permaground Copper U-Bolt Ground Clamp, Conductor Range 250-2/0 Sol, Pipe Size 2in, Ground Rod Sizes 2 to 2-3/8in, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4/0 Sol - 2/0 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 2/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	2-1/8
NPS/IPS Pipe Size	2

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	4.665
Height BX (IN)	5.125
Height (mm)	118.491
Length (IN)	3.625
Length (mm)	92.075
Weight (LB)	1.241
Weight BX (LB)	15.087
Width (IN)	1.562
Width BX (IN)	6.25
Width (mm)	39.6748

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA

Material	Copper
Wire Binding Hardware Material	Silicon bronze

Additional Technical Specifications

Conductor Type	Stranded

Bolt and Screw Sizes

Clamping Bolt Size	1/4
Number of Wire Binding Screws per Port	0
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366926262

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440