**SKU:** GPL-39

**UPC:** 0783669262728

**Features & Benefits:**

**Description:**Permaground Copper U-Bolt Ground Clamp, Conductor Range 2/0-4 Sol, Pipe Size 2-1/2in, Ground Rod Sizes 2-1/2 to 2-7/8in, UL, CSA

# Specs

## *Additional Class Attributes*

| | |
|---|---|
| **Connection** | Mechanical |
| **Number of Conductors** | 1 |
| **Number of Ports / Wireways** | 1 |
| **Wire Orientation** | Perpendicular |

## *Conductor Ranges*

| | |
|---|---|
| **Conductor Range AL Solid (Secondary, tap, load)** | NA |
| **Conductor Range AL Stranded (Primary, run, main, line)** | NA |
| **Conductor Range AL Stranded (Secondary, tap, load)** | NA |
| **Conductor Range CU Solid (Primary, run, main, line)** | 2/0 Sol - 4 Sol |
| **Conductor Range CU Solid (Secondary, tap, load)** | NA |
| **Conductor Range CU Stranded (Primary, run, main, line)** | 2/0 Str - 4 Str |
| **Conductor Range CU Stranded (Secondary, tap, load)** | NA |
| **Conductor Range AL Solid (Primary, run, main, line)** | NA |
| **Ground Rod Size** | 2-1/2 |
| **NPS/IPS Pipe Size** | 2-1/2 |

## *Dimensions*

| | |
|---|---|
| **Drive Size Main** | 3/8 |
| **Drive Type Main** | External Hex |
| **Height (IN)** | 5.165 |
| **Height BX (IN)** | 5.125 |
| **Height (mm)** | 131.191 |
| **Length (IN)** | 4.25 |
| **Length (mm)** | 107.95 |
| **Weight (LB)** | 1.568 |
| **Weight BX (LB)** | 19.011 |
| **Width (IN)** | 1.6 |
| **Width BX (IN)** | 6.25 |
| **Width (mm)** | 40.64 |

## *Material and Finish*

| | |
|---|---|
| **Conductor Material** | Copper |
| **Connector Finish** | NA |
| **Insulation** | NA |

| | |
|---|---|
| **Material** | Copper |
| **Wire Binding Hardware Material** | Silicon bronze |

## *Additional Technical Specifications*

| | |
|---|---|
| **Conductor Type** | Stranded |

## *Bolt and Screw Sizes*

| | |
|---|---|
| **Clamping Bolt Size** | 1/4 |
| **Number of Wire Binding Screws per Port** | 0 |
| **Wire Binding Screw Size** | NA |

## *General*

| | |
|---|---|
| **Bag Quantity** | 1 |
| **Carton Quantity Description** | STD PACK QTY 12 |
| **Direct Burial** | Yes |
| **Dual Rated** | No |
| **NEMA Code** | 0-000-1 |
| **UPC Code** | 78366926272 |

## *Testing Standards*

| | |
|---|---|
| **CSA File Number** | LR-29601 |
| **CSA Standard** | C22.2 No. 65-03 |
| **Prop65 Compliance** | WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov |
| **UL Control Number** | 667P |
| **UL / CULUS Specification** | UL 467 Listed |
| **UL File Number** | E34440 |