



SKU: GPL-6

UPC: 0783669262100

Features & Benefits:

Description:Permaground Copper U-Bolt Ground Clamp, Conductor Range 250-2/0 Sol, Pipe Size 3/8in, Ground Rod Sizes 5/8 to 3/4in, Rebar Size #6, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges


Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4/0 Sol - 2/0 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 2/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8
NPS/IPS Pipe Size	3/8
Rebar Size(s) Main	#6 (3/4)

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	2.875
Height BX (IN)	4.875
Height (mm)	73.025
Length (IN)	2.25
Length (mm)	57.15
Weight (LB)	0.686
Weight BX (LB)	4.286
Width (IN)	1.562
Width BX (IN)	3.875
Width (mm)	39.6748

Material and Finish

Conductor Material	Copper
Connector Finish	NA



Stranded

NA

78366926210

E34440