



**SKU:** GPL3903BU

**UPC:** 0783669945478

**Features & Benefits:**

**Description:**Permaground Copper Waterpipe Ground Clamp, Conductor Range 4/0-4, Pipe Size 1-1/4 to 2in, UL

## Specs

### Additional Class Attributes

|                            |               |
|----------------------------|---------------|
| Connection                 | Mechanical    |
| Number of Conductors       | 1             |
| Number of Ports / Wireways | 1             |
| Wire Orientation           | Perpendicular |

### Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | NA              |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 4/0 Str - 4 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |
| Fits Pipe O.D. Range                                   | 1.66 - 2.38     |
| NPS/IPS Pipe Size                                      | 1-1/2           |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 3/8          |
| Drive Type Main | External Hex |
| Height (IN)     | 4.102        |
| Height BX (IN)  | 4.5          |
| Height (mm)     | 104.1908     |
| Length (IN)     | 4.333        |
| Length (mm)     | 110.0582     |
| Weight (LB)     | 0.725        |
| Width (IN)      | 1.475        |
| Width BX (IN)   | 6.875        |
| Width (mm)      | 37.465       |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Bronze |
| Insulation         | NA     |
| Material           | Copper |

### *Additional Technical Specifications*

Conductor Type

Stranded

### *Bolt and Screw Sizes*

Clamping Bolt Size 1/4

Number of Wire Binding Screws per Port 0

Wire Binding Screw Size NA

### *General*

Bag Quantity 1

Carton Quantity Description STD PACK QTY 10

Direct Burial Yes

Dual Rated No

NEMA Code S-573-2

UPC Code 78366994547

### *Testing Standards*

Prop65 Compliance WARNING: Cancer and Reproductive Harm -  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

UL Control Number 667P

UL / CULUS Specification UL 467 Listed

UL File Number E34440