




SKU: GPL3908BU

UPC: 0783669945522

Features & Benefits:

Description:Permaground Copper Waterpipe Ground Clamp, Conductor Range 4/0-4, Pipe Size 10in, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Fits Pipe O.D. Range	10.75
NPS/IPS Pipe Size	10

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	11.544
Height BX (IN)	8.5
Height (mm)	293.2176
Length (IN)	12.625
Length (mm)	320.675
Weight (LB)	2.012
Width (IN)	1.475
Width BX (IN)	11.5
Width (mm)	37.465

Material and Finish

Conductor Material	Copper
Connector Finish	Bronze
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Clamping Bolt Size	1/4
Number of Wire Binding Screws per Port	0
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366994552

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440