**SKU:** GR-33

**UPC:** 0783669004625

**Features & Benefits:**

**Description:**Permaground Copper Ground Clamp, Conductor Range 250-2/0 Sol, 3 Conductors, Pipe Size 2in, UL

## Specs

### *Additional Class Attributes*

| | |
|---|---|
| **Connection** | Mechanical |
| **Number of Conductors** | 3 |
| **Number of Ports / Wireways** | 3 |
| **Wire Orientation** | Parallel |

### *Conductor Ranges*

| | |
|---|---|
| **Conductor Range AL Solid (Secondary, tap, load)** | NA |
| **Conductor Range AL Stranded (Primary, run, main, line)** | NA |
| **Conductor Range AL Stranded (Secondary, tap, load)** | NA |
| **Conductor Range CU Solid (Primary, run, main, line)** | 4/0 Sol - 2/0 Sol |
| **Conductor Range CU Solid (Secondary, tap, load)** | NA |
| **Conductor Range CU Stranded (Primary, run, main, line)** | 250 kcmil - 2/0 Str |
| **Conductor Range CU Stranded (Secondary, tap, load)** | NA |
| **Conductor Range AL Solid (Primary, run, main, line)** | NA |
| **NPS/IPS Pipe Size** | 2 |

### *Dimensions*

| | |
|---|---|
| **Drive Size Main** | 1/2 |
| **Drive Type Main** | External Hex |
| **Height (IN)** | 5 |
| **Height BX (IN)** | 6.5 |
| **Length (IN)** | 1.75 |
| **Weight (LB)** | 2.3952 |
| **Weight BX (LB)** | 9.5808 |
| **Width (IN)** | 5.25 |
| **Width BX (IN)** | 12.75 |

### *Material and Finish*

| | |
|---|---|
| **Conductor Material** | Copper |
| **Insulation** | NA |
| **Material** | Copper |

### *Additional Technical Specifications*

| | |
|---|---|
| **Conductor Type** | Stranded |

## Bolt and Screw Sizes

| | |
|---|---|
| **Clamping Bolt Size** | 5/16 |
| **Number of Wire Binding Screws per Port** | 0 |
| **Wire Binding Screw Size** | NA |

## General

| | |
|---|---|
| **Bag Quantity** | 1 |
| **Carton Quantity Description** | STD PACK QTY 3 |
| **Direct Burial** | Yes |
| **Dual Rated** | No |
| **NEMA Code** | 0-000-1 |
| **UPC Code** | 78366900462 |

## Testing Standards

| | |
|---|---|
| **Prop65 Compliance** | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| **UL Control Number** | 8M24 |
| **UL / CULUS Specification** | UL/cUL 467 Listed |
| **UL File Number** | E158587 |

## Color

| | |
|---|---|
| **Color** | Copper |