



SKU: GT-31

UPC: 0783669005141

Features & Benefits:

Description:Permaground Copper Ground Clamp, Conductor Range 2/0-4 Sol, 2 Conductors, Pipe Size 2in, Perpendicular Orientation, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Ports / Wireways	2
Wire Orientation	Perpendicular

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 4 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 4 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	2/0 Sol - 4 Sol
NPS/IPS Pipe Size	2

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	4.125
Height BX (IN)	6.5
Length (IN)	2.875
Weight (LB)	1.074
Weight BX (LB)	4.296
Width (IN)	2
Width BX (IN)	12.75

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper



Additional Technical Specifications

Conductor Type

Solid

Bolt and Screw Sizes

Clamping Bolt Size 1/4

Number of Wire Binding Screws per Port 0

Wire Binding Screw Size NA

General

Bag Quantity 1

Carton Quantity Description STD PACK QTY 3

Direct Burial Yes

Dual Rated No

NEMA Code 0-000-1

UPC Code 78366900514

Testing Standards

CSA File Number NA

Prop65 Compliance This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number 8M24

UL / CULUS Specification UL/cUL 467 Listed

UL File Number E158587