



SKU: GT2-250-W/C

UPC: 0783669367096

Features & Benefits:

Description: Aluminum Multiple Tap Connector, Dual Rated, Main Conductor Range 250-2, Tap Range 250-2, 2 Parallel Taps, Tin Plated, UL, Includes Cover

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	3
Number of Poles	1
Number of Ports Tap	2
Replacement Part(s)	Cover
Type of Accessory	NA
Wire Orientation	Parallel

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.18
Height BX (IN)	2.75
Height (mm)	55.372
Length (IN)	3.332
Length (mm)	84.6328
Weight (LB)	0.612
Weight BX (LB)	2.0842
Width (IN)	3.375
Width BX (IN)	6
Width (mm)	85.725

Material and Finish

Clamping Hardware Finish	Tin
Clamping Hardware Material	Aluminum
Conductor Material	Copper
Connector Finish	Tin
Insulation	Supplied with insulating cover
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------



Bolt and Screw Sizes

Clamping Bolt Size	5/8-18
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366936709

Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------