



SKU: GTA-2-2-KIT

UPC: 0783669342680

Features & Benefits:

Description: Aluminum Parallel Tap Connector Kit, Dual Rated, Main Conductor Range 2-12, Tap Range 2-12 AL, 2-14 CU, Tin Plated, UL, CSA, With De-Ox, Includes Cover

Specs

Additional Class Attributes

Connection	Mechanical
Includes	GTA-2-2, GTC-2, 5cc pack of De-Ox
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Type of Accessory	GTC-2
Wire Orientation	Parallel

Dimensions

Drive Size Main	NA
Drive Size Tap	NA
Drive Type Main	Slotted
Drive Type Tap	Slotted
Height (IN)	1.6
Height BX (IN)	3.75
Height (mm)	40.64
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.0919341418290873
Weight BX (LB)	1.685
Width (IN)	4
Width BX (IN)	6.5
Width (mm)	101.6

Material and Finish

Clamping Hardware Finish	Tin
Clamping Hardware Material	Steel
Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Bolt and Screw Sizes

Clamping Bolt Size	5/16-24
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/16
Wire Binding Torque	2 AWG = 50

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366934268

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 12 Sol
Conductor Range AL Stranded (Primary, run, main, line)	2 Str - 12 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 12 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 12 Sol

Voltage

Voltage Rating	600 V
----------------	-------