



SKU: GTA-750-750

UPC: 0783669342604

Features & Benefits:

Description: Aluminum Parallel Tap Connector, Dual Rated, Main Conductor Range 750-500, Tap Range 750-1/0, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Type of Accessory	GTPC-750-750
Wire Orientation	Parallel

Dimensions

Drive Size Main	1/2
Drive Size Tap	1/2
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	2.235
Height BX (IN)	2.75
Height (mm)	56.769
Length (IN)	3.172
Length (mm)	80.5688
Weight (LB)	1.115
Weight BX (LB)	6.9367
Width (IN)	2.625
Width BX (IN)	6
Width (mm)	66.675

Material and Finish

Clamping Hardware Finish	Tin
Clamping Hardware Material	Aluminum
Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------



Bolt and Screw Sizes

Clamping Bolt Size	15/16-16
Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	15/16
Wire Binding Torque	500

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366934260

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 500 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	750 kcmil - 1/0 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 500 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	750 kcmil - 1/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------