

SKU: GU-22

UPC: 0783669003727

Features & Benefits:

Description:Permaground Copper Ground Clamp, Conductor Range 500-300, 2 Conductors, Pipe Size 3in



Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Ports / Wireways	2
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 300 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
NPS/IPS Pipe Size	3

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	6
Height BX (IN)	6
Length (IN)	1.5
Weight (LB)	0.49
Weight BX (LB)	1.96
Width (IN)	5.25
Width BX (IN)	7.5

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper



Additional Technical Specifications

Conductor Type

Stranded

Bolt and Screw Sizes

Clamping Bolt Size 5/16

Number of Wire Binding Screws per Port 0

Wire Binding Screw Size NA

General

Bag Quantity 1

Carton Quantity Description STD PACK QTY 3

Direct Burial No

Dual Rated No

NEMA Code 0-000-1

UPC Code 78366900372

Testing Standards

Prop65 Compliance This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number NA

UL File Number NA

Color

Color

Copper