



SKU: HGSE-020

UPC: 0783669006025

Features & Benefits:

Description: Permaground Copper Transformer Ground Clamp, Conductor Range 2/0-8 Sol, Two-Way Basket

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	1.938
Height BX (IN)	6.5
Length (IN)	2
Mounting Bolt/Stud Size (mm)	30810.2
Weight (LB)	0.625
Weight BX (LB)	63.125
Width (IN)	1.25
Width BX (IN)	12.75

Material and Finish

Clamping Hardware Material	Steel
Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	3/8
Clamping Bolt Size (mm)	965.2
Mounting Bolt/Stud Size	1/2-13
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/2-13



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366900602

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	2/0 Sol - 8 Sol