



**SKU:** HL21-1

**UPC:** 0783669460162

**Features & Benefits:**

**Description:** Cast Bronze Mechanical Lug, Conductor Range 4/0-2/0, 1 Port, 1 Hole, 3/8in Bolt Size, UL

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Mounting Hole Type         | Thru       |
| Number of Conductors       | 1          |
| Number of Mounting Holes   | 1          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 1          |

### Dimensions

|                              |              |
|------------------------------|--------------|
| Drive Size Main              | 3/8          |
| Drive Type Main              | External Hex |
| Height (IN)                  | 0            |
| Height BX (IN)               | 2.25         |
| Length (IN)                  | 0            |
| Mounting Bolt/Stud Size (mm) | 965.2        |
| Weight (LB)                  | 0.4127       |
| Weight BX (LB)               | 4.6143       |
| Width (IN)                   | 0            |
| Width BX (IN)                | 5            |

### Material and Finish

|                    |             |
|--------------------|-------------|
| Conductor Material | Copper      |
| Connector Finish   | NA          |
| Insulation         | NA          |
| Material           | Cast bronze |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |     |
|----------------------------------------|-----|
| Mounting Bolt/Stud Size                | 3/8 |
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Screw Size                | NA  |

## General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 9 |
| Direct Burial               | No             |
| Dual Rated                  | No             |
| NEMA Code                   | S-588-3        |
| UPC Code                    | 78366946016    |

## Testing Standards

|                          |                                                                                                               |
|--------------------------|---------------------------------------------------------------------------------------------------------------|
| CSA File Number          | NA                                                                                                            |
| Prop65 Compliance        | WARNING: Cancer and Reproductive Harm -<br><a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number        | 8M24                                                                                                          |
| UL / CULUS Specification | UL 486A/B Listed                                                                                              |
| UL File Number           | E158587                                                                                                       |

## Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

## Color

|       |        |
|-------|--------|
| Color | Bronze |
|-------|--------|

## Conductor Ranges

|                                                        |                   |
|--------------------------------------------------------|-------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                |
| Conductor Range AL Stranded (Primary, run, main, line) | NA                |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                |
| Conductor Range CU Stranded (Primary, run, main, line) | 4/0 Str - 2/0 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                |
| Wire Combinations                                      | NA                |

## Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|