



SKU: HL75-2N

UPC: 0783669460346

Features & Benefits:

Description: Cast Bronze Mechanical Lug, Conductor Range 750-500, 1 Port, 2 Holes, 1/2in Bolt Size, UL

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	3.5
Length (IN)	0
Mounting Bolt/Stud Size (mm)	304.8
Weight (LB)	1.7544
Weight BX (LB)	10.7853
Width (IN)	0
Width BX (IN)	5.875

Material and Finish

Connector Finish	NA
Insulation	NA
Material	Cast bronze

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366946034

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 500 kcmil
Wire Combinations	NA

Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E158587

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Bronze
-------	--------

Voltage

Voltage Rating	35 kV
----------------	-------