



SKU: IKB-800

UPC: 0783669480061

Features & Benefits:

Description: Copper Two-Bolt Split Bolt, Main Conductor Range 800-400, Tap Range 800-3/0, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1

Dimensions

Drive Size Main	NA
Drive Type Main	External Hex
Height (IN)	2.825
Height BX (IN)	2
Height (mm)	71.755
Length (IN)	2.538
Length (mm)	64.4652
Weight (LB)	1.2686583993315
Width (IN)	1.688
Width BX (IN)	6.1875
Width (mm)	42.8752

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	NA

General



Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366948006

Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	800 kcmil - 400 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	800 kcmil - 3/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------