




SKU: PBT2-4-250-F

UPC: 0783669728514

Features & Benefits:

Description: Nimbus4Flex Insulated Aluminum Multi-Tap Connector, Conductor Range 250-6, Flex 4/0-6 H,I,K 2/0-6 M 3/0-6 DLO, 4 Ports, Dual Sided Entry, Double, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	4
Number of Poles	1
Number of Ports / Wireways	4
Number of Usable Ports	4
Replacement Part(s)	Cap

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.046
Height BX (IN)	3.625
Height (mm)	51.9684
Length (IN)	2.11
Length (mm)	53.594
Max Insulation OD (IN)	0.75
Max Insulation OD (mm)	19.05
Weight (LB)	0.125
Weight BX (LB)	2.654
Width (IN)	3.198
Width BX (IN)	6.375
Width (mm)	81.2292

Material and Finish

Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	335

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366972851

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	4/0-6 H,I,K 2/0-6 M 3/0-6 DLO

Color

Color	Black
-------	-------

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C