



SKU: PBT2-6-600-F

UPC: 0783669728576

Features & Benefits:

Description: Nimbus4Flex Insulated Aluminum Multi-Tap Connector, Conductor Range 600-4, Flex 350-4 H,I,K 4/0-4 M 373.7-4 DLO, 6 Ports, Dual Sided Entry, Double, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Mounting Hole Type	NA
Number of Conductors	6
Number of Poles	1
Number of Ports / Wireways	6
Number of Usable Ports	6
Replacement Part(s)	Cap

Dimensions

Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	3.039
Height BX (IN)	3.625
Height (mm)	77.1906
Length (IN)	4.062
Length (mm)	103.1748
Max Insulation OD (IN)	1.115
Max Insulation OD (mm)	28.321
Weight (LB)	0.638
Weight BX (LB)	2.7848
Width (IN)	4.281
Width BX (IN)	6.375
Width (mm)	108.7374

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	13/16
Wire Binding Torque	500

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366972857

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	600 kcmil - 4 Str
Conductor Range AL Stranded (Secondary, tap, load)	600 kcmil - 4 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	600 kcmil - 4 Str
Conductor Range CU Stranded (Secondary, tap, load)	600 kcmil - 4 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	350-4 H,I,K 4/0-4 M 373.7-4 DLO

Voltage

Voltage Rating	600 V
----------------	-------

Color

Cap Color Main	Blue
Cap Color Tap	Blue
Color	Black

Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
Flammability Rating	Insulation rated per UL 94
Temperature Rating	90°C

