



SKU: PED-4-350-CP-Z

UPC: 0783669711844

Features & Benefits:

Description: Insulated Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 350-10, 4 Ports

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	4
Number of Poles	1
Number of Ports / Wireways	4
Replacement Part(s)	R0130C00A - PULL TAB PLUG, RED P-24X, R0132C00A - PULL TAB PLUG, RED P-27X

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.645
Height BX (IN)	3.75
Height (mm)	67.183
Length (IN)	4.781
Length (mm)	121.4374
Weight (LB)	0.894954531690219
Weight BX (LB)	8.1852
Width (IN)	3.753
Width BX (IN)	6.5
Width (mm)	95.3262

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	11/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971184

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Clear
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol

Voltage

Voltage Rating	600 V
----------------	-------