



**SKU:** PED-4-350-Z

**UPC:** 0783669699104

**Features & Benefits:**

**Description:** Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 350-6, 4 Ports, UL

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Number of Conductors       | 4          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 4          |

### Dimensions

|                 |                   |
|-----------------|-------------------|
| Drive Size Main | 5/16              |
| Drive Type Main | Internal Hex      |
| Height (IN)     | 1.25              |
| Height BX (IN)  | 2.75              |
| Height (mm)     | 31.75             |
| Length (IN)     | 4.53              |
| Length (mm)     | 115.062           |
| Weight (LB)     | 0.429980213592176 |
| Weight BX (LB)  | 1.7268            |
| Width (IN)      | 1                 |
| Width BX (IN)   | 5                 |
| Width (mm)      | 25.4              |

### Material and Finish

|                                |          |
|--------------------------------|----------|
| Conductor Material             | Aluminum |
| Connector Finish               | Tin      |
| Insulation                     | NA       |
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Tin      |
| Wire Binding Hardware Material | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |   |
|----------------------------------------|---|
| Number of Wire Binding Screws per Port | 1 |
|----------------------------------------|---|



Wire Binding Screw Size

11/16

### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 3 |
| Direct Burial               | No             |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-588-4        |
| UPC Code                    | 78366969910    |

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                   |
|--------------------------------------------------------|-------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                |
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|