



SKU: PED-4-750-SS-Z

UPC: 0783669712124

Features & Benefits:

Description: SafetySub Insulated Multi-Tap Connector, Dual Rated, Direct Burial, Conductor Range 750-2, 4 Ports

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	4
Number of Poles	1
Number of Ports / Wireways	4
Replacement Part(s)	500/750-CAP - CAP FOR 500-750 PESS, R0129C00A - PULL TAB PLUG, RED P-25

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	3.898
Height BX (IN)	7
Height (mm)	99.0092
Length (IN)	6.973
Length (mm)	177.1142
Weight (LB)	3.61278408152781
Weight BX (LB)	5.205
Width (IN)	6.53
Width BX (IN)	8
Width (mm)	165.862

Material and Finish

Conductor Material	Aluminum
Connector Finish	Clear
Insulation	EPDM
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes



Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	15/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366971212

Testing Standards

ANSI Specification	ANSI C119.1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Black
-------	-------

Voltage

Voltage Rating	600 V
----------------	-------