



**SKU:** PED10-350SS-DB

**UPC:** 0783669712230

**Features & Benefits:**

**Description:** SafetySub Insulated Multi-Tap Connector, Dual Rated, Direct Burial, Conductor Range 350-12, 10 Ports, UL, CSA

## Specs

### Additional Class Attributes

|                            |                                                               |
|----------------------------|---------------------------------------------------------------|
| Connection                 | Mechanical                                                    |
| Number of Conductors       | 10                                                            |
| Number of Poles            | 1                                                             |
| Number of Ports / Wireways | 10                                                            |
| Replacement Part(s)        | R2314C00A - PLUG FOR ROCKET SEAL, R2315C00A - SCREW PORT PLUG |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 5/16         |
| Drive Type Main | Internal Hex |
| Height (IN)     | 0            |
| Height BX (IN)  | 6            |
| Length (IN)     | 0            |
| Weight (LB)     | 0.9469       |
| Weight BX (LB)  | 2.2938       |
| Width (IN)      | 0            |
| Width BX (IN)   | 10.75        |

### Material and Finish

|                                |                               |
|--------------------------------|-------------------------------|
| Connector Finish               | Tin                           |
| Insulation                     | TPE (thermoplastic elastomer) |
| Material                       | Aluminum                      |
| Wire Binding Hardware Finish   | Tin                           |
| Wire Binding Hardware Material | Aluminum                      |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |     |
|----------------------------------------|-----|
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Screw Size                | 3/4 |



### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 2 |
| Direct Burial               | Yes            |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-569-1        |
| UPC Code                    | 78366971223    |

### Testing Standards

|                   |                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------|
| CSA File Number   | LR-29601                                                                                                   |
| CSA Standard      | C22.2 No. 198.2                                                                                            |
| Prop65 Compliance | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |

### Conductor Ranges

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 12 Str |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 12 Sol    |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 12 Str |
| Conductor Range AL Solid (Primary, run, main, line)    | 10 Sol - 12 Sol    |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|       |       |
|-------|-------|
| Color | Black |
|-------|-------|

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|