

SKU: PET-6-500-Z

UPC: 0783669710205

Features & Benefits:

Description: Aluminum Spade Type Transformer Lug, Dual Rated, Conductor Range 500-2, 6 Ports

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	6
Number of Poles	1
Number of Ports / Wireways	6

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.625
Height BX (IN)	2.75
Height (mm)	41.275
Length (IN)	10.156
Length (mm)	257.9624
Weight (LB)	1.418
Weight BX (LB)	4.5017
Width (IN)	1
Width BX (IN)	6
Width (mm)	25.4

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1

Wire Binding Screw Size	3/4

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971020

Testing Standards

ANSI Specification	ANSI C119.6
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA