




SKU: PET-6-750-Z

UPC: 0783669710267

Features & Benefits:

Description: Aluminum Spade Type Transformer Lug, Dual Rated, Conductor Range 750-1/0, 6 Ports

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	6
Number of Poles	1
Number of Ports / Wireways	6

Dimensions

Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	1.75
Height BX (IN)	3.75
Height (mm)	44.45
Length (IN)	11.312
Length (mm)	287.3248
Weight (LB)	1.78615465006651
Weight BX (LB)	2.9152
Width (IN)	1.188
Width BX (IN)	6.5
Width (mm)	30.1752

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
--	---



Wire Binding Screw Size

15/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971026

Testing Standards

ANSI Specification	ANSI C119.6
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 1/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 1/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA