



SKU: PG810-S-Z

UPC: 0783669730128

Features & Benefits:

Description: Aluminum Parallel Groove Clamp, Dual Rated, Conductor Range 1/0-8 Sol, 3/8in Steel Bolt

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	9/16
Drive Type Main	Carriage
Height (IN)	2.208
Height BX (IN)	7
Height (mm)	56.0832
Length (IN)	1.125
Length (mm)	28.575
Weight (LB)	0.214
Weight BX (LB)	11.016
Width (IN)	1.674
Width BX (IN)	8
Width (mm)	42.5196

Material and Finish

Clamping Hardware Material	Steel
Conductor Material	Copper
Connector Finish	Clear
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes



Clamping Bolt Size	3/8
Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366973012

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
-------------------	---

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	1/0 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	1/0 Sol - 8 Sol