

SKU: PICS-64

UPC: 0783669232875

Features & Benefits:

Description: Aluminum Insulated Service Entrance Sleeve, Dual Rated, Main Conductor Range 4 Sol - 6, Tap Range 4 Sol - 6, Blue Color Code, Die Index ND-BG

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Flared End	No
ILSCOs Die Index Number	ND-BG

Dimensions

Height (IN)	0.72
Height BX (IN)	3.75
Height (mm)	18.288
Length (IN)	2.81
Length (mm)	71.374
Weight (LB)	0.055
Weight BX (LB)	2.945
Width (IN)	0.72
Width BX (IN)	6
Width (mm)	18.288

Material and Finish

Conductor Material	Aluminum
Connector Finish	NA
Insulation	Nylon
Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	0-000-1
UPC Code	78366923287

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA

Testing Standards

ANSI Specification	ANSI C119.4
CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
RUS Listed	Yes
UL Control Number	NA
UL File Number	NA

Environment and Temperature

Temperature Rating	NA

Color

Color	Black
Color Code	Blue
Color Code Secondary	Blue

Conductor Ranges

Conductor Range ACSR (Secondary, tap, load)	6 ACSR
Conductor Range ACSR (primary, run, main, line)	6 ACSR
Conductor Range AL Solid (Secondary, tap, load)	4 Sol - 6 Sol
Conductor Range AL Stranded (Primary, run, main, line)	4 Str - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	4 Str - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	4 Sol
Conductor Range CU Solid (Secondary, tap, load)	4 Sol - 6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	4 Str - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	4 Sol - 6 Sol