



SKU: PICS-76

UPC: 0783669232974

Features & Benefits:

Description: Aluminum Insulated Service Entrance Sleeve, Dual Rated, Main Conductor Size 1/0, Tap Range 2 Sol - 4, Yellow Color Code, Die Index ND-BG

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Flared End	No
ILSCOs Die Index Number	ND-BG

Dimensions

Height (IN)	0.72
Height BX (IN)	3.75
Height (mm)	18.288
Length (IN)	2.81
Length (mm)	71.374
Weight (LB)	0.0436606962193008
Weight BX (LB)	2.563
Width (IN)	0.72
Width BX (IN)	6.375
Width (mm)	18.288

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	Nylon
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	0-000-1
UPC Code	78366923297



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

ANSI Specification

ANSI C119.4

CSA File Number

NA

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

RUS Listed

Yes

UL Control Number

NA

UL File Number

NA

Environment and Temperature

Temperature Rating

NA

Color

Color

Black

Color Code

Yellow

Color Code Secondary

Orange

Conductor Ranges

Conductor Range ACSR (Secondary, tap, load)

1/0 ACSR

Conductor Range ACSR (primary, run, main, line)

4 ACSR

Conductor Range AL Solid (Secondary, tap, load)

2 Sol - 4 Sol

Conductor Range AL Stranded (Primary, run, main, line)

1/0 Str

Conductor Range AL Stranded (Secondary, tap, load)

2 Str - 4 Str

Conductor Range CU Solid (Primary, run, main, line)

NA

Conductor Range CU Solid (Secondary, tap, load)

2 Sol - 4 Sol

Conductor Range CU Stranded (Primary, run, main, line)

1/0 Str

Conductor Range CU Stranded (Secondary, tap, load)

2 Str - 4 Str

Conductor Range AL Solid (Primary, run, main, line)

2 Sol - 4 Sol