



SKU: PSA-4-750-Z

UPC: 0783669699302

Features & Benefits:

Description: Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 750-1/0, 4 Ports

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	4
Number of Poles	1
Number of Ports / Wireways	4
Replacement Part(s)	PSC-4-750

Dimensions

Drive Size Main	3/8
Drive Type Main	Internal Hex
Height (IN)	2
Height BX (IN)	3.5
Height (mm)	50.8
Length (IN)	6.562
Length (mm)	166.6748
Weight (LB)	2.43915067100427
Weight BX (LB)	5.5097
Width (IN)	2.5
Width BX (IN)	5.875
Width (mm)	63.5

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes



Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	15/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366969930

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	750 kcmil - 1/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA