



**SKU:** PSA-8-750-Z

**UPC:** 0783669699340



**Features & Benefits:**

**Description:** Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 750-1/0, 8 Ports

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Number of Conductors       | 8          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 8          |
| Replacement Part(s)        | PSC-8-750  |

### Dimensions

|                 |                  |
|-----------------|------------------|
| Drive Size Main | 3/8              |
| Drive Type Main | Internal Hex     |
| Height (IN)     | 2                |
| Height BX (IN)  | 3.75             |
| Height (mm)     | 50.8             |
| Length (IN)     | 13.187           |
| Length (mm)     | 334.9498         |
| Weight (LB)     | 4.90913663962384 |
| Weight BX (LB)  | 10.4402          |
| Width (IN)      | 2.5              |
| Width BX (IN)   | 6.5              |
| Width (mm)      | 63.5             |

### Material and Finish

|                                |          |
|--------------------------------|----------|
| Conductor Material             | Copper   |
| Connector Finish               | Tin      |
| Insulation                     | NA       |
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Tin      |
| Wire Binding Hardware Material | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes



|                                        |       |
|----------------------------------------|-------|
| Number of Wire Binding Screws per Port | 2     |
| Wire Binding Screw Size                | 11/16 |

### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 2 |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-588-4        |
| UPC Code                    | 78366969934    |

### Testing Standards

|                   |                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------|
| Prop65 Compliance | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number | NA                                                                                                         |
| UL File Number    | NA                                                                                                         |

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                     |
|--------------------------------------------------------|---------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                  |
| Conductor Range AL Stranded (Primary, run, main, line) | 750 kcmil - 1/0 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                  |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                  |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                  |
| Conductor Range CU Stranded (Primary, run, main, line) | 750 kcmil - 2 Str   |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                  |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                  |