



SKU: PTA26-500-4/0

UPC: 0783669740257

Features & Benefits:

Description: Aluminum Multi-Tap Connector, Dual Rated, Main Conductor Range 500-4/0, Tap Range 4/0-6, 2-14, 2 Main Ports, 6 Tap Ports, Tin Plated, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	8
Number of Poles	1
Number of Ports Tap	6
Type of Accessory	Cover - (1) RO614WOOA & (1) RO615WOOA
Wire Orientation	Parallel

Dimensions

Drive Size Main	3/8
Drive Size Tap	3/8
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	3.234
Height BX (IN)	2.25
Height (mm)	82.1436
Length (IN)	3.515
Length (mm)	89.281
Weight (LB)	1.24
Weight BX (LB)	2.1409
Width (IN)	1.25
Width BX (IN)	5
Width (mm)	31.75

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16
Wire Binding Torque	275

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366974025

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	(2) 10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 4/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	(4) 4/0 Str - 6 Str / (2) 2 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	(2) 10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 4/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	(4) 4/0 Str - 6 Str / (2) 2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------