



**SKU:** PTT-2L-250-Z

**UPC:** 0783669750157

**Features & Benefits:**

**Description:** Aluminum Pole Type Overhead Transformer Lug, Dual Rated, Conductor Range 250-10, 2 Ports, Left Handed

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Number of Conductors       | 2          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 2          |

### Dimensions

|                                |              |
|--------------------------------|--------------|
| Drive Size Main                | 5/16         |
| Drive Type Main                | Internal Hex |
| Height (IN)                    | 1.125        |
| Height BX (IN)                 | 2.25         |
| Length (IN)                    | 2.391        |
| Length (mm)                    | 60.7314      |
| Mounting Bolt/Stud Length (mm) | 101.6        |
| Mounting Bolt/Stud Size (mm)   | 304.8        |
| Weight (LB)                    | 0.439        |
| Weight BX (LB)                 | 2.122        |
| Width (IN)                     | 4            |
| Width BX (IN)                  | 5            |
| Width (mm)                     | 101.6        |

### Material and Finish

|                                |          |
|--------------------------------|----------|
| Conductor Material             | Copper   |
| Connector Finish               | Tin      |
| Insulation                     | NA       |
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Tin      |
| Wire Binding Hardware Material | Aluminum |

### Additional Technical Specifications

|                |       |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

### Bolt and Screw Sizes

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 1/2 |
|-------------------------|-----|



|                                        |       |
|----------------------------------------|-------|
| Number of Wire Binding Screws per Port | 1     |
| Wire Binding Screw Size                | 11/16 |

### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 2 |
| Direct Burial               | No             |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-588-4        |
| UPC Code                    | 78366975015    |

### Testing Standards

|                    |                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------|
| ANSI Specification | ANSI C119.6                                                                                                |
| Prop65 Compliance  | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number  | NA                                                                                                         |
| UL File Number     | NA                                                                                                         |

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                 |
| Conductor Range AL Stranded (Primary, run, main, line) | 250 kcmil - 10 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                 |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol             |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                 |
| Conductor Range CU Stranded (Primary, run, main, line) | 250 kcmil - 10 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                 |
| Conductor Range AL Solid (Primary, run, main, line)    | 10 Sol             |