



SKU: RE-050-1P1X-A

UPC: 0783669015348

Features & Benefits:

Description: Surgency Surge Protection, Residential, Lead Wire Size 12, 1 Phase, Single System, 50kA Surge Current, 120 V, UL, CSA

Specs

Additional Class Attributes

AC Frequency	50/60
Mounting Method	Mountable or flush mountable with flush mount kit
Warranty	5 Year

Additional Technical Specifications

Nominal Voltage	120 V
-----------------	-------

Conductor Ranges

Conduit Hub Size	1/2
Lead Wire Size	12 AWG

Material and Finish

Insulation	NA
Material	Polycarbonate

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
NEMA Code	0-000-1
ULCSA Type	1
UPC Code	78366901534

Testing Standards

CSA File Number	NA
CSA Standard	C22.2 No. 269.1-14
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	E315947
UL / CULUS Specification	UL 1449 Listed
UL File Number	E484255



Environment and Temperature

Environmental Conditions
Operating Temperature

Enclosure rated to NEMA/UL Type 1/2/3/3R/3X/4/4X
-40°C to 65°C

Surge Specifications

Dry relaying contact	No
Electrical Noise Filter	No
Nominal Discharge Current	20 kA
Outlet	None
Phase	1
Short Circuit Current Rating (SCCR)	200 kA
Surge Current Rating	50 kA
System	Single
UL Voltage Protection Rating L-G	700
UL Voltage Protection Rating L-L	NA
UL Voltage Protection Rating L-N	700
UL Voltage Protection Rating N-G	1200