



SKU: RE-050-1R1X-D2

UPC: 0783669014303

Features & Benefits:

Description: Surgency Surge Protection, Residential, Lead Wire Size 12, 1 Phase, Split System, 50kA Surge Current, 120/240 V, Noise Filter, UL, CSA

Specs

Additional Class Attributes

AC Frequency	50/60 Hz
Mounting Method	Mountable or flush mountable with flush mount kit
Warranty	5 Year

Additional Technical Specifications

Nominal Voltage	120/240 V
-----------------	-----------

Conductor Ranges

Conduit Hub Size	1/2
Lead Wire Size	12 AWG

Dimensions

Height (IN)	3.3
Height BX (IN)	5.375
Length (IN)	3.3
Weight (LB)	1.25
Weight BX (LB)	1.75
Width (IN)	3.2
Width BX (IN)	5.375

Material and Finish

Insulation	NA
Material	Polycarbonate

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
NEMA Code	0-000-1
ULCSA Type	2
UPC Code	78366901430



Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL / CULUS Specification

UL 1449 Listed

Environment and Temperature

Environmental Conditions

Enclosure rated to NEMA/UL Type 1/2/3/3R/3X/4/4X

Operating Temperature

-40°C to 65°C

Surge Specifications

Electrical Noise Filter	Yes
Nominal Discharge Current	20 kA
Outlet	None
Phase	1
Short Circuit Current Rating (SCCR)	200 kA
Surge Current Rating	50 kA
System	Split
UL Voltage Protection Rating L-G	700
UL Voltage Protection Rating L-L	1200
UL Voltage Protection Rating L-N	NA
UL Voltage Protection Rating N-G	NA