



SKU: RLT-8

UPC: 0783669715767

Features & Benefits:

Description:Permaground Copper Grounding Connector, Main Conductor Range 500-300, Tap Range 500-300, Ground Rod Size 5/8in, Rebar Sizes #5-#6, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Catalog Number	ILD-998
ILSCOs Die Index Number	998

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 300 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	500 kcmil - 300 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8
Rebar Size(s) Main	#6 (3/4)

Dimensions

Height (IN)	2.142
Height BX (IN)	4.75
Height (mm)	54.4068
Length (IN)	1.234
Length (mm)	31.3436
Weight (LB)	0.37603087517285
Weight BX (LB)	4.062
Width (IN)	0.875
Width BX (IN)	7
Width (mm)	22.225

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper



Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366971576

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-5465
CSA Standard	C22.2 No. 41
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------