



SKU: SCNL-27

UPC: 0783669960334

Features & Benefits:

Description: Aluminum Solar Combiner Node Lay-In, Dual Rated, Main Conductor Range 4-14, Tap Range 750-1/0, 27 Main Ports, 1 Tap Port, Tin Plated, UL

Specs

Dimensions

Dimension G (IN)	0.443
Dimension G (mm)	11.2522
Drive Size Main	NA
Drive Size Tap	5/16
Drive Type Main	Slotted
Drive Type Tap	External Hex
Height (IN)	1.8
Height BX (IN)	2.25
Length (IN)	3.186
Mounting Hole Diameter (IN)	0.343
Mounting Hole Diameter (mm)	8.7122
Mounting Hole Spacing (IN)	2.3
Mounting Hole Spacing (mm)	58.42
Weight (LB)	0.145
Weight BX (LB)	0.8926
Width (IN)	3.05
Width BX (IN)	5
Width (mm)	77.47

Material and Finish

Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 14 AWG = 35

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 5
NEMA Code	S-588-3
UPC Code	78366996033



Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation