SKU: SE-050-3N4X-C

UPC: 0783669010411

Features & Benefits:

Description: Surgency Surge Protection, Service Entrance, Lead Wire Size 10, 3 Phase, Delta System, 50kA Surge Current, 480 V, Indicator LED, Noise Filter, UL, CSA

Specs

Additional Class Attributes

AC Frequency	50/60 Hz
Mounting Method	Mountable or flush mountable with flush mount kit
Type Of Indicators	Blue indicator LED
Warranty	5 Year

Additional Technical Specifications

Nominal Voltage	480 V

Conductor Ranges

Conduit Hub Size	3/4
Lead Wire Size	10 AWG

Dimensions

Height (IN)	6.466
Height BX (IN)	4
Height (mm)	164.2364
Length (IN)	4.805
Length (mm)	122.047
Weight (LB)	1.9
Weight BX (LB)	2.65
Width (IN)	3.543
Width BX (IN)	6
Width (mm)	89.9922

Material and Finish

Insulation	NA
Material	Polycarbonate

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1

NEMA Code	0-000-1
ULCSA Type	2
UPC Code	78366901041

Testing Standards

CSA File Number	NA
CSA Standard	C22.2 No. 269.2-13
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	E315947
UL / CULUS Specification	UL 1283 Listed
UL File Number	E484255

Environment and Temperature

Environmental Conditions	Enclosure rated to NEMA/UL Type 1/2/3/3R/3X/4/4X
Operating Temperature	-40°C to 65°C

Surge Specifications

Dry relaying contact	No
Electrical Noise Filter	Yes
Nominal Discharge Current	20 kA
Outlet	None
Phase	3
Short Circuit Current Rating (SCCR)	200 kA
Surge Current Rating	50 kA
System	Delta
UL Voltage Protection Rating L-G	1800
UL Voltage Protection Rating L-L	4000
UL Voltage Protection Rating L-N	NA
UL Voltage Protection Rating N-G	NA