



SKU: SGB-1/0

UPC: 0783669960341

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 1/0-14, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Ports / Wireways	2
Wire Orientation	Parallel

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	1.423
Height BX (IN)	3.75
Height (mm)	36.1442
Length (IN)	1.508
Weight (LB)	0.113
Weight BX (LB)	11.87
Width (IN)	0.625
Width BX (IN)	6

Material and Finish

Clamping Hardware Finish	Nickel Strick, Zinc, Green Dye
Clamping Hardware Material	Stainless steel
Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	3/8-24
Clamping Bolt Size (mm)	97129.6



Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8
Wire Binding Torque	8 AWG = 40

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Dual Rated	Yes
NEMA Code	S-573-6
UPC Code	78366996034

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	1/0 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol