



SKU: SK-1000

UPC: 0783669819175

Features & Benefits:

Description: Copper Split Bolt, Conductor Range for Equal Main & Tap
1000-350, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1

Dimensions

Drive Size Main	2-1/4
Drive Type Main	External Hex
Height (IN)	4
Height BX (IN)	2.75
Height (mm)	101.6
Length (IN)	2.959
Length (mm)	75.1586
Weight (LB)	0.90563410325539
Weight BX (LB)	3.2224
Width (IN)	2.563
Width BX (IN)	4
Width (mm)	65.1002
Wire Diameter Range Primary (IN)	0.682 - 1.162

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366981917

Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 188
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	460C
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 350 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	1000 kcmil - 350 kcmil
Conductor Range for Equal Run & Tap ACSR	900 ACSR - 300 ACSR
Conductor Range for Equal Run & Tap Str	1000 kcmil - 350 kcmil
Conductor Range for Equal Run & Tap Sol	NA
Conductor Range for Minimum Tap with Maximum Run	4/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------