



SKU: SPA-2

UPC: 0783669857009

Features & Benefits:

Description: Aluminum Splicer/Reducer, Dual Rated, Conductor Range 2-14, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Number of Ports / Wireways	2
Wire Orientation	Parallel

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.55
Height BX (IN)	2.25
Length (IN)	1.19
Weight (LB)	0.030824349307667
Weight BX (LB)	1.493
Width (IN)	0.45
Width BX (IN)	5

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	1



Wire Binding Screw Size

5/16

Wire Binding Torque

8 AWG = 40

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366985700

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	2 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Voltage

Voltage Rating	35 kV
----------------	-------