



SKU: SPDS-4

UPC: 0783669233148

Features & Benefits:

Description: Permaground Bronze Service Post Connector, Male, Conductor Range 1-8 Sol, 3/8-16 x 5/8in Stud Size, Short Stud, Double Conductor, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Drive Size Main	11/16
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	3.75
Length (IN)	0
Mounting Bolt/Stud Size (mm)	96926.4
Weight (LB)	0.1865
Weight BX (LB)	9.5201
Width (IN)	0
Width BX (IN)	6

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Bronze

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8-16
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366923314

Testing Standards

CSA File Number	AP-100973-1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E158587

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Bronze
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------