


SKU: T3A2-1000N

UPC: 0783669903133



Features & Benefits:

Description: Aluminum Mechanical Lug, Dual Rated, Conductor Range 1000-500, 3 Ports, 6 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Tin Plated, UL, CSA, Same as T3A4-1000N

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	3
Number of Mounting Holes	6
Number of Poles	1
Number of Ports / Wireways	3

Dimensions

Dimension G (IN)	0.625
Dimension G (mm)	15.875
Drive Size Main	1/2
Drive Type Main	Internal Hex
Height (IN)	1.813
Height BX (IN)	2
Length (IN)	5.97
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Tang Length (IN)	3.625
Tang Length (mm)	92.075
Tang Thickness (IN)	0.5
Tang Thickness (mm)	12.7
Tang Width (IN)	4.875
Tang Width (mm)	123.825
Weight (LB)	2.098
Weight BX (LB)	2.2456
Width (IN)	4.875
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Voltage

Voltage Rating

35 kV