



SKU: TLK-4

UPC: 0783669879063

Features & Benefits:

Description: Aluminum Transformer Lug Kit, Dual Rated, Includes (29) TA-600, (18) 3/8-16 x 2 Bolts, (18) 3/8-16 Free Spin Flange Nuts

Specs

Additional Class Attributes

Contains DE-OX®	No
Includes	(29) TA-600, (18) 3/8-16 X (2) Bolts, (18) 3/8-16 Free Spin Flange Nuts

Dimensions

Height (IN)	3.875
Height BX (IN)	3.75
Height (mm)	98.425
Length (IN)	11
Length (mm)	279.4
Weight (LB)	5.94577557530637
Weight BX (LB)	12.4049
Width (IN)	6.375
Width BX (IN)	6.375
Width (mm)	161.925

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366987906

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03



Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

453G

UL / CULUS Specification

UL 486A/B Listed

UL File Number

E6207

Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Voltage

Transformer kVA Size

500 (3-PHASE)

Voltage Rating

35 kV