



SKU: UCS-350-Z

UPC: 0783669929768

Features & Benefits:

Description: Aluminum Utility Compression Sleeve, Dual Rated, Conductor Size 350

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	14
Installing Dies	655
Sight Window	No

Dimensions

Height (IN)	1.156
Height BX (IN)	2.75
Height (mm)	29.3624
Inside Diameter (IN)	0.703
Inside Diameter (mm)	17.8562
Length (IN)	5.3
Length (mm)	134.62
Outside Diameter (IN)	1.156
Outside Diameter (mm)	29.3624
Weight (LB)	0.332632682796394
Weight BX (LB)	2.0936
Width (IN)	1.156
Width BX (IN)	5
Width (mm)	29.3624

Material and Finish

Conductor Material	Aluminum
Connector Finish	Wax
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366992976

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	NA

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA