



SKU: ULT-11-Z

UPC: 0783669930863

Features & Benefits:

Description:Permabond Copper Grounding C Crimp, Main Conductor
Range 4/0-3/0 Sol, Tap Range 2/0-1/0 Sol, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	D3

Dimensions

Height (IN)	1.628
Height BX (IN)	2
Height (mm)	41.3512
Length (IN)	1
Length (mm)	25.4
Weight (LB)	0.285
Weight BX (LB)	7.2719
Width (IN)	1.075
Width BX (IN)	6.188
Width (mm)	27.305

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366993086



Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

CSA File Number

LR-29601

CSA Standard

C22.2 No. 65-03

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

ROHS Indicator

IND

UL Control Number

453G

UL / CULUS Specification

UL 467 Listed

UL File Number

E6207

Environment and Temperature

Temperature Rating

90°C

Color

Color

Copper

Color Code

NA

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

4/0 Sol - 3/0 Sol

Conductor Range CU Solid (Secondary, tap, load)

2/0 Sol - 1/0 Sol

Conductor Range CU Stranded (Primary, run, main, line)

4/0 Str - 3/0 Str

Conductor Range CU Stranded (Secondary, tap, load)

2/0 Str - 1/0 Str

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

35 kV