SKU: USPA-1/0SSP-DB

UPC: 0783669941166

Features & Benefits:

Description: Streetwise Street Light Connector, Dual Rated, Direct Bury, Conductor Range 1/0-14, 1 Port Line Side, 1 Port Load Side, UL, With De-Ox

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	2
Number of Ports Tap	1
Number of Ports / Wireways	2

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	5.63
Height BX (IN)	2
Length (IN)	1.925
Weight (LB)	0.168
Weight BX (LB)	0.651
Width (IN)	0.93
Width BX (IN)	6.188

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	TPE (thermoplastic elastomer)
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8

General

Bag Quantity	0
Carton Quantity Description	STD PACK QTY 3
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366994116

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 198.2
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	88X4
UL / CULUS Specification	UL/cUL 486D Listed
UL File Number	E125087

Environment and Temperature

Temperature Rating	90°C
Water tight	Yes

Color

Color	Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	10 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	10 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Voltage

Voltage Rating	600 V