



**SKU:** USPA-350SS-DB

**UPC:** 0783669941104

**Features & Benefits:**

**Description:** Watertight Underground In-Line Splice, Dual Rated, Direct Bury, Conductor Range 350-10, UL, CSA



## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Number of Conductors       | 2          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 2          |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 5/16         |
| Drive Type Main | Internal Hex |
| Height (IN)     | 2.89         |
| Height BX (IN)  | 3.75         |
| Length (IN)     | 9.07         |
| Weight (LB)     | 0.5          |
| Weight BX (LB)  | 1.895        |
| Width (IN)      | 1.25         |
| Width BX (IN)   | 6.5          |

### Material and Finish

|                                |          |
|--------------------------------|----------|
| Conductor Material             | Copper   |
| Connector Finish               | Wax      |
| Insulation                     | EPDM     |
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Wax      |
| Wire Binding Hardware Material | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |     |
|----------------------------------------|-----|
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Torque                    | 350 |



## General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 3 |
| Direct Burial               | Yes            |
| Dual Rated                  | Yes            |
| NEMA Code                   | S-569-2        |
| UPC Code                    | 78366994110    |

## Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 198.2                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| RUS Listed               | Yes                                                                                                                 |
| UL Control Number        | 88X4                                                                                                                |
| UL / CULUS Specification | UL 486D Listed                                                                                                      |
| UL File Number           | E125087                                                                                                             |

## Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
| Water tight        | Yes  |

## Color

|       |       |
|-------|-------|
| Color | Black |
|-------|-------|

## Conductor Ranges

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                 |
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 10 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                 |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                 |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                 |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 10 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                 |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                 |

## Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|