



SKU: VT-4-S

UPC: 0783669954050

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 4-14, 1 Port, 2 Holes, #10 Bolt Size, 1/2in Hole Spacing, Seamless, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.25
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.469
Height BX (IN)	2.25
Height (mm)	11.9126
Length (IN)	1.75
Length (mm)	44.45
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.234
Mounting Hole Diameter (mm)	5.9436
Mounting Hole Spacing (IN)	0.5
Mounting Hole Spacing (mm)	12.7
Tang Length (IN)	1
Tang Length (mm)	25.4
Tang Thickness (IN)	0.122
Tang Thickness (mm)	3.0988
Tang Width (IN)	0.5
Tang Width (mm)	12.7
Weight (LB)	0.037
Weight BX (LB)	4.62
Width (IN)	0.5
Width BX (IN)	5
Width (mm)	12.7

Material and Finish

Conductor Material	Copper
Connector Finish	NA



Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Torque	10 - 18 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366995405

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA



Voltage

Voltage Rating

35 kV